



CHIEF FIRE OFFICER

THE CAYMAN ISLANDS FIRE SERVICE

SELF INSPECTION CHECKLIST

The purpose of this document is to aid the property/business owner or operator with guidance to applicable requirements for fire safety inspections.

Any item with ** requires service report UPON inspection.

Exits/Means of Egress
Exit doors unlocked/unblocked.
Exit access is unobstructed.
Exterior of exit doors are clear Exit doors are operable.
Enclosed exit stairways clear and free of storage.
Exit lights are operable.
No added surface bolts/latches on exit doors.
Exit doors readily distinguishable as such, with no mirrors or other coverings over doors.
Fire Protection Systems
Fire alarm, fire sprinkler and suppression systems are inspected and tested annually. **
Sprinkler fire pump is tested annually.
Wet standpipe system is flow tested every year.
Dry standpipe system is hydro-tested every 5 years.
Sprinkler connection (FDC) is unobstructed and accessible.
FDC caps in place and FDC couplings freely spin.
Sprinkler heads are unobstructed with no storage with-in 18 inches
Sprinkler heads are free of paint, corrosion, or other debris.
Sprinkler valve rooms are accessible and free of storage, and their location indentified.
Fire alarm devices (pull stations, control panels, etc.) are accessible.
Fire alarm monitored by UL central station.
Fire Alarm Control Panel (FACP) accessible and location indentified.
Fire alarm system horns and strobes are not obstructed.
Kitchen hood suppression system inspected at 6 month intervals. **
Kitchen hood vent system inspected and cleaned at required intervals. **
Kitchen hood suppression system remote pull is accessible.
Fire extinguishers serviced, inspected and tagged annually. **
Fire extinguishers are accessible and mounted.





CHIEF FIRE OFFICER

THE CAYMAN ISLANDS FIRE SERVICE

Fire Protection Assemblies
Fire doors are operable by self closing and latching.
Fire doors are not wedged or propped open.
Roll down fire doors drop tested by outside testing agency each year. **
Fire rated walls, floor, and ceiling construction not breached
No obstructions blocking operation of fire doors.
Hazardous materials
Fire Department notified of any changes in chemical storage or processes.
No open containers of flammable or combustible liquids.
Compressed gas cylinders secured upright.
Fuel dispensing hoses are not worn or cracked.
Electrical
Emergency lights tested by outside agency each year.
Emergency generator is fully tested annually. **
Extension cords not used in place of permanent wiring.
Outlet/switch/electrical covers in place.
Covers for junction boxes, panels, etc. are in place.
Electrical rooms are identified as such.
Housekeeping
No accumulation of combustible materials/waste.
Electrical, mechanical, boiler rooms are accessible and free of storage.
Electrical equipment and motors free of debris and build-up (i.e. sawdust, lint, etc.).
Miscellaneous
Privately-owned fire hydrants accessible.
Fire Vehicle Access and access road unobstructed.
If required, KNOX Key Box installed, and keys updated.
Elevators should have the current inspection certificate displayed.